

Roulement à aiguilles RNA6912-UU-IKO - RNA6912-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna6912-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r (*)
68	—	—	RNA 6912UU	—	505	68	85	45	1
Standard mounting diameter D_s Max. mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (rpm) (2)					
80		93 400	186 000	3 000					

Notes: (*) Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379500
Diam. intérieur	68 mm
Diam. extérieur	85 mm
Épaisseur	45 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE