

Roulement à aiguilles RNA6918-U-IKO - RNA6918-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna6918-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|--|---------------------------------------|--|---------------------------------------|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 105 | — | — | — | RNA 6918U | 1 360 | 105 | 125 | 63 | 1.1 |
| Standard mounting diameter D_s Max. mm | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (2) rpm | | | | | | |
| 118.5 | 172 000 | 471 000 | 1 800 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952379807 |
| Diam. intérieur | 105 mm |
| Diam. extérieur | 125 mm |
| Épaisseur | 63 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE