

## Roulement à aiguilles RNA4920-UU-IKO - RNA4920-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna4920-uu-iko>

**I KO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
115	RNA 4920UU	—	—	—	1 200	115	140	40	1.1
Standard mounting dimension $D_A$ Max. mm	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm						
133.5	134 000	297 000	1 700						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	I KO
N° Ean13	3663952379869
Diam. intérieur	115 mm
Diam. extérieur	140 mm
Épaisseur	40 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE