

## Roulement à aiguilles RNA4913-U-IKO - RNA4913-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rna4913-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
72	---	<b>RNA 4913U</b>	---	---	325	72	90	25	1.3
Standard rounding dimension $D_s$ Max. mm	N	N	N	N					
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed(2)						
	85	56 800	99 800	2 500					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952380131
Diam. intérieur	72 mm
Diam. extérieur	90 mm
Épaisseur	25 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE