

Roulement à aiguilles NA4901-U-IKO - NA4901-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4901-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 12 | — | NA 4901U | — | — | 27.5 | 12 | 24 | 13 | 14 |

| r_s min (1) | F_w | Standard mounting dimensions (mm) | | D_s Max. | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed(2) rpm | Assembled inner ring |
|------------------|-------|-----------------------------------|------|---------------|--------------------------------|-----------------------------------|--------------------------------------|----------------------|
| | | Min. | Max. | | | | | |
| 0.3 | 16 | 14 | 15 | 22 | 8 470 | 9 320 | 12 000 | LRTZ 121614 |

Notes(1) Minimum allowable value of shaft dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952381077 |
| Diam. intérieur | 12 mm |
| Diam. extérieur | 24 mm |
| Épaisseur | 14 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE