

## Roulement à aiguilles NA4902-U-IKO - NA4902-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4902-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
15	—	NA 4902U	—	—	36	15	28	13	14

  

$r_s$ min (1)	$F_w$	Standard mounting dimensions (mm)		$d_1$ Min.	$D_1$ Max.	Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.						
0.3	20	17	19	26	9 570	11 600	9 500	LRTZ 152014	

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381121
Diam. intérieur	15 mm
Diam. intérieur	0.591" inch
Diam. extérieur	28 mm
Diam. extérieur	1.102" inch
Epaisseur	14 mm
Epaisseur	0.551" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE