


## Roulement à aiguilles NA6906-U-IKO - NA6906-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na6906-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
30	—	—	—	—	NA 6906U	185	30	47	30	31

$r_s$ min (1)	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	$d_s$				
0.3	35	32	34	45	40 100	63 000	5 500	LRTZ 303531

Notes(1)  
(1) Minimum allowable value of shaft dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381398
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	31 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE