

Roulement à aiguilles NA4910-U-IKO - NA4910-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4910-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		μ	d	D	C
50	—	NA 4910U	—	—	295	50	72	22	23

r_s min (¹⁾)	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed(²) rpm	Assembled inner ring
		Min.	Max.	D_w Max.				
0.6	58	54	57	68	41 300	71 100	3 500	LRTZ 505823

Notes: (¹) Minimum allowable value of chamfer dimension r.
(²) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381589
Diam. intérieur	50 mm
Diam. extérieur	72 mm
Épaisseur	23 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE