

## Roulement à aiguilles NA4910-U-IKO - NA4910-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4910-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$\mu$	d	D	C
50	—	NA 4910U	—	—	295	50	72	22	23

  

$r_s$ min	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	$D_w$ Max.				
0.6	58	54	57	68	41 300	71 100	3 500	LRTZ 505823

Notes: (1) Minimum allowable value of shaft diameter  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381589
Diam. intérieur	50 mm
Diam. extérieur	72 mm
Épaisseur	23 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE