

Roulement à aiguilles NA6912-U-IKO - NA6912-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na6912-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|------------------|-----------------------------------|---------------|----------------------------------|-----------------------------------|---|---------------------------|-----|-----|-----|-----|
| | With two seals | With one seal | With two seals | With one seal | | g | d | D | C | B |
| 60 | — | — | — | — | NA 6912U | 785 | 60 | 85 | 45 | 46 |
| r_s min | Standard mounting dimensions (mm) | | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed ⁽¹⁾ | Assembled inner ring | | | | |
| 1 | 68 | 65 66 80 | N 93 400 | N 186 000 | rpm 3 000 | LRTZ 608846 | | | | |

Notes: (1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952381671 |
| Diam. intérieur | 60 mm |
| Diam. extérieur | 85 mm |
| Épaisseur | 46 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE