

Roulement à aiguilles
NA6915-UU-IKO - NA6915-UU-IKO

https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na6915-uu-iko



MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, With Inner Ring



NA6915-UU

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
75	—	—	NA 6915UU	—	1 480	75	105	54	55

r _s min (1)	F _N	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed (2) rpm	Assembled inner ring	
		d _s Min.	D _s Max.					
1	85	80	83	100	128 000	299 000	2 000	LRTZ 758555

Notes (1) Minimum allowable value of chamber dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: (1) The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381800
Diam. intérieur	75 mm
Diam. extérieur	105 mm
Epaisseur	55 mm
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE