


Roulement à aiguilles NA6916-UU-IKO - NA6916-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na6916-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
80	—	—	NA 6916UU	—	1 570	80	110	54	55

r _s min (1)	F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 809055
		d _s Min.	d _s Max.	D _s Max.				
1	90	85	88	105	132 000	317 000	2 000	

Notes: (1) Minimum allowable value of shaft dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381848
Diam. intérieur	80 mm
Diam. extérieur	110 mm
Épaisseur	55 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE