

Roulement à aiguilles NA6919-U-IKO - NA6919-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na6919-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
95	—	—	—	—	NA 6919U	2 600	95	130	63	64

r_s min	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d_s Min.	D_s Max.					
1.1	110	101.5	108	123.5	177 000	493 000	1 700	LRTZ 9511064

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381954
Diam. intérieur	95 mm
Diam. intérieur	3.74" inch
Diam. extérieur	130 mm
Diam. extérieur	5.118" inch
Epaisseur	64 mm
Epaisseur	2.52" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE