

Roulement à aiguilles NA4920-U-IKO - NA4920-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4920-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
100	—	NA 4920U	—	—	1 980	100	140	40	41

r _s min ⁽¹⁾ F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 10011541
	d _s Min.	d _s Max.	D _s Max.				
1.1	115	106.5	113	133.5	134 000	297 000	1 700

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381985
Diam. intérieur	100 mm
Diam. extérieur	140 mm
Épaisseur	41 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE