

## Roulement à aiguilles NA4922-UU-IKO - NA4922-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4922-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$d$	$D$	$C$	$B$
110	NA 4922UU				2 150	110	150	40	41

  

$r_s$ mm	$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring	
		$d_s$ Min.	$d_s$ Max.					
1.1	125	116.5	123	143.5	140 000	322 000	1 500	LRTZ 11012541

Notes: (1) Minimum allowable value of shaft diameter  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382005
Diam. intérieur	110 mm
Diam. extérieur	150 mm
Épaisseur	41 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE