

Roulement à aiguilles NA4926-UU-IKO - NA4926-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4926-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
130	NA 4926UU				4 080	130	180	50	51

r_s min	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		d_s Min.	D_s Max.				
1.5	150	138	148	206 000	511 000	1 300	LRTZ 13015051

Notes: (1) Minimum allowable value of outer diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382043
Diam. intérieur	130 mm
Diam. intérieur	5.118" inch
Diam. extérieur	180 mm
Diam. extérieur	7.087" inch
Epaisseur	51 mm
Epaisseur	2.008" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE