

Roulement à aiguilles NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4928-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	NA 4928UU				4 340	140	190	50	51

r_s min	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRTZ 14016051
		d_s Min.	D_s Max.				
1.5	160	148	158	214 000	549 000	1 200	

Notes:
⁽¹⁾ Minimum allowable value of shaft diameter r
⁽²⁾ Allowable rotational speed applies to grease lubrication.
 Remark:
 1. This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382050
Diam. intérieur	140 mm
Diam. extérieur	190 mm
Épaisseur	51 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE