

## Roulement à aiguilles NA4928-U-IKO - NA4928-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/na4928-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	—	NA 4928U	—	—	4 340	140	190	50	51

$r_s$ min	$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring	
		$d_s$ Min.	$d_s$ Max.					
1.5	160	148	158	182	214 000	549 000	1 200	LRTZ 14016051

Notes:  
(1) Minimum allowable value of shaft diameter  $r$   
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382067
Diam. intérieur	140 mm
Diam. extérieur	190 mm
Épaisseur	51 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE