

## Roulement à aiguilles BR162416-U-IKO - BR162416-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/br162416-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
25.400 (1)		<b>BR 162416 U</b>	83	25.400 (1)	38.100 (1 1/2)	25.400 (1)
Standard mounting dimensions mm		Basic dynamic load rating $C_0$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup>		
$D_1$ Max.	$r_{as}$ max	N	N	rpm		
32.9	1.0	23 600	31 300	8 000		

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382142
Diam. intérieur	25.4 mm
Diam. extérieur	38.1 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE