

Roulement à aiguilles BR364828-U-IKO - BR364828-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/br364828-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
57.150 (2 1/4)		BR 364828 U	459	57.150 (2 1/4)	76.200 (3)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating C_0	Basic static load rating C_0	Allowable rotational speed ⁽²⁾		
D_1 Max.	F_{is} max ⁽¹⁾	N	N	rpm		
69.0	1.5	90 300	158 000	3 500		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382333
Diam. intérieur	57.15 mm
Diam. extérieur	76.2 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE