


## Roulement à aiguilles BR486028-U-IKO - BR486028-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/br486028-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>76.200</b> (3)		<b>BR 486028 U</b>	585	76.200 (3 )	95.250 (3 7/8)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating $C_0$	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_1$ Max.	$r_{as}$ max	N	N	rpm		
87.0	2.0	105 000	211 000	2 500		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382388
Diam. intérieur	76.2 mm
Diam. extérieur	95.25 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE