



Roulement à aiguilles
BRI61816-U-IKO - BRI61816-U-IKO

https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri61816-u-iko

**MACHINED TYPE NEEDLE ROLLER BEARINGS**
With Seal, With Inner Ring, Inch Series



Identification number		Mass (Ref.)	Boundary dimensions mm(inch)					
Shaft dia. mm (inch)	With two seals		With one seal	d	D	C	B	
9.525 ($\frac{3}{8}$)		BRI 61816 U	79	9.525 ($\frac{3}{8}$)	28.575 (1 $\frac{1}{8}$)	25.400 (1)	25.650	
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
	Min.	Max.				d_s	$r_{as\ max}$	
15.875 ($\frac{5}{8}$)	14	14.5	24.5	0.6	18 300	20 000	12 000	LRBZ 61016 B

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to grease lubrication.

Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382470
Diam. intérieur	9.525 mm
Diam. extérieur	28.575 mm
Epaisseur	25.4 mm
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE