


## Roulement à aiguilles BRI142620-U-IKO - BRI142620-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri142620-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>22.225</b> ( $\frac{7}{8}$ )		<b>BRI 142620 U</b>	177	22.225 ( $\frac{7}{8}$ )	41.275 (1 $\frac{3}{4}$ )	31.750 (1 $\frac{1}{4}$ )	32.000
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
	Min.	Max.				$r_{as max}$ <sup>(1)</sup>	
	27	36.0	34 900	49 900	7 000	LRBZ 141820 B	

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382555
Diam. intérieur	22.225 mm
Diam. extérieur	41.275 mm
Épaisseur	31.75 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE