


Roulement à aiguilles BRI162820-UU-IKO - BRI162820-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri162820-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		g	d	D	C	B
25.400 (1)	BRI 162820 UU		196	25.400 (1)	44.450 (1 $\frac{1}{4}$)	31.750 (1 $\frac{1}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	$r_{as max}$ ⁽¹⁾					
	30.5	30.7	39.2	36 000	53 500	6 500	LRBZ 162020 B	

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382579
Diam. intérieur	25.4 mm
Diam. extérieur	44.45 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE