

Roulement à aiguilles BRI264120-U-IKO - BRI264120-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri264120-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		g	d	D	C	B
41.275 (1 5/8)		BRI 264120 U	386	41.275 (1 5/8)	65.088 (2 5/8)	31.750 (1 1/4)	32.000	
F_w	Standard mounting dimensions (mm)				Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 263220 B
	Min.	Max.	d_s	$r_{as max}$ ⁽¹⁾				
50.800 (2)	48	49	57.8	1	51 000	89 400	4 000	

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382685
Diam. intérieur	41.275 mm
Diam. extérieur	65.088 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE