

## Roulement à aiguilles BRI284828-UU-IKO - BRI284828-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri284828-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		$g$	$d$	$D$	$C$	$B$
<b>44.450</b> (1 3/4)	<b>BRI 284828 UU</b>		804	44.450 (1 3/4)	76.200 (3 )	44.450 (1 3/4)	44.700	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring <b>LRBZ 283628 B</b>	
	Min.	Max.	$r_{as max}$ <sup>(1)</sup>					
57.150 (2 1/4)	52.5	55	69.0	1.5	90 300	158 000	3 500	

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382708
Diam. intérieur	44.45 mm
Diam. extérieur	76.2 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE