



Roulement à aiguilles
BRI325228-U-IKO - BRI325228-U-IKO

https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/bri325228-u-iko

**MACHINED TYPE NEEDLE ROLLER BEARINGS**
With Seal, With Inner Ring, Inch Series



Identification number		Mass (Ref.)	Boundary dimensions mm(inch)				
Shaft dia. mm (inch)	With two seals		With one seal	d	D	C	B
50.800 (2)	BRI 325228 U		889	50.800 (2)	82.550 (3 1/4)	44.450 (1 3/4)	44.700

F_w	Standard mounting dimensions (mm)			Bore dynamic load rating C	Bore static load rating C_0	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	$r_{as\ max}$ ⁽¹⁾					
63.500 (2 1/2)	58	61	74.3	1.5	94 600	174 000	3 000	LRBZ 324028 B

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to grease lubrication.

Remark: 1. The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382722
Diam. intérieur	50.8 mm
Diam. extérieur	82.55 mm
Epaisseur	44.45 mm
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE