

Roulement à aiguilles
GBR162416-UU-IKO - GBR162416-UU-IKO

https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr162416-uu-iko

MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
25.400 (1)	GBR 162416 UU		99	25.400	38.100	25.400
Standard mounting dimensions mm						
D_s Max.	r_{se} max (°)	Basic dynamic load rating C_0 N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm		
33.3	0.6	31 000	46 100	3 000		

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Allowable rotational speed applies to grease lubrication.

Remark: The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382906
Diam. intérieur	25.4 mm
Diam. extérieur	38.1 mm
Epaisseur	25.4 mm
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE