

Roulement à aiguilles GBR283720-UU-IKO - GBR283720-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr283720-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
44.450 (1.75)	GBR 283720 UU		230	44.450 ¹⁾²⁾	58.738 ²⁾³⁾	31.750 ¹⁾²⁾
Standard mounting dimensions mm				Allowable rotational speed ⁴⁾		
D_A	r as max	Seal dynamic load rating C_1	Seal static load rating C_0	rpm		
53.7	0.6	58 900	114 000	1 800		

Notes: 1) Minimum allowable value of chamfer dimension r
2) Allowable rotational speed applies to grease lubrication.
3) The outer ring has an oil groove and an oil hole.
4) Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383033
Diam. intérieur	44.45 mm
Diam. extérieur	58.738 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE