


Roulement à aiguilles GBR303920-UU-IKO - GBR303920-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr303920-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
47.625 (1 7/8)	GBR 303920 UU		240	47.625 ⁽¹⁾ _(1 7/8)	61.912 ⁽²⁾ _(2 41/64)	31.750 ⁽¹⁾ _(1 1/4)
Standard mounting dimensions mm		Ball dynamic load rating C_0	Ball static load rating C_0	Allowable rotational speed ⁽²⁾		
D_A	r as max	N	N	rpm		
56.2	1	61 100	121 000	1 700		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383040
Diam. intérieur	47.625 mm
Diam. extérieur	61.912 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE