


Roulement à aiguilles GBR607632-U-IKO - GBR607632-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbr607632-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
95.250 (3 7/8)	GBR 607632 U		1 320	95.250 (3 7/8)	120.650 (4 7/8)	50.800 (2)
Standard mounting dimensions mm		Ball dynamic load rating C_1	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
112.6	1.5	175 000	371 000	850		

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383224
Diam. intérieur	95.25 mm
Diam. intérieur	3 3/4" inch
Diam. extérieur	120.65 mm
Diam. extérieur	4 3/4" inch
Epaisseur	50.8 mm
Epaisseur	2" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE