


Roulement à aiguilles GBRI122416-U-IKO - GBRI122416-U-IKO

https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri122416-u-iko

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
19.050 ($\frac{3}{4}$)	GBRI 122416 U		143	19.050 ($\frac{7}{8}$)	38.100 (1 $\frac{1}{2}$)	25.400 (1)			
B	F _w	Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min. d _s	Max. d _s	D _s Max.					r _{as} max. ⁽¹⁾
25.650	25.400 (1)	24	24.4	33.3	0.6	31 000	46 100	3 000	LRBZ 121616

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383330
Diam. intérieur	19.05 mm
Diam. extérieur	38.1 mm
Épaisseur	25.4 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE