


## Roulement à aiguilles GBR1243920-U-IKO - GBR1243920-U-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/gbri243920-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
38.100 (1 1/2)	GBR1243920 U		400	38.100 (1 1/2)	61.912 (2 3/8)	31.750 (1 1/4)			
B	F <sub>w</sub>	Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min. d <sub>s</sub>	Max. d <sub>s</sub>	D <sub>s</sub> Max.					r <sub>as</sub> max. <sup>(1)</sup>
32.000	47.625 (1 7/8)	43.3	45	56.2	1	61 100	121 000	1 700	LRBZ 243020

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383460
Diam. intérieur	38.1 mm
Diam. extérieur	61.912 mm
Épaisseur	31.75 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE