

Roulement à aiguilles RNAFW172520-IKO - RNAFW172520-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/rnafw172520-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
Without inner ring

| Shaft dia. mm | Identification number | Mass (Ref.) g | Boundary dimensions mm | | | | Standard mounting dimensions mm | | | Basic dynamic load rating C N | Basic static load rating C ₀ N |
|------------------|-----------------------|---------------------|------------------------|----|----|--|---------------------------------|------------------------|----------------|-------------------------------------|---|
| | | | F _d | D | C | r ⁽¹⁾ r _{s min} | d _b | D _s Max. | D _b | | |
| 17 | RNAFW 172520 | 33,5 | 17 | 25 | 20 | 0,3 | 20,6 | 23 | 17,6 | 12 400 | 17 900 |

Allowable rotational speed⁽²⁾
rpm
30 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952383828 |
| Diam. intérieur | 17 mm |
| Diam. extérieur | 25 mm |
| Épaisseur | 20 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE