

## Roulement à aiguilles NAF152813-IKO - NAF152813-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/naf152813-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring

| Shaft dia.<br>mm               | Identification number                      | Mess (Ref.)<br>g                          | Boundary dimensions mm |    |    |                                   |                | Standard mounting dimensions mm |                        |                        |                |      |
|--------------------------------|--|---|------------------------|----|----|-----------------------------------|----------------|---------------------------------|------------------------|------------------------|----------------|------|
|                                |  |   | d                      | D  | C  | r <sub>s</sub> min <sup>(1)</sup> | F <sub>w</sub> | d <sub>b</sub><br>Max.          | D <sub>s</sub><br>Min. | d <sub>s</sub><br>Max. | D <sub>b</sub> |      |
| 15                             | <b>NAF 152813</b>                          | 38.5                                      | 15                     | 28 | 13 | 0.3                               | 20             | 23.6                            | 28                     | 17                     | 19             | 20.6 |
| Basic dynamic load rating<br>C | Basic static load rating<br>C <sub>0</sub> | Allowable rotational speed <sup>(2)</sup> | Assembled inner ring   |    |    |                                   |                |                                 |                        |                        |                |      |
| N                              | N  | rpm                                       | LRT 152013             |    |    |                                   |                |                                 |                        |                        |                |      |
| 9 590                          | 13 500                                     | 25 000                                    |                        |    |    |                                   |                |                                 |                        |                        |                |      |

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952384436 |
| Diam. intérieur | 15 mm         |
| Diam. extérieur | 28 mm         |
| Épaisseur       | 13 mm         |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE