


## Roulement à aiguilles NAU4924-IKO - NAU4924-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nau4924-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings



Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> r <sub>s min</sub>	J	E <sub>w</sub>
120	—	NAU 4924	2 680	120	165	45	1.5	138	153.5
Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm							
146 000	268 000	3 000							

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952385754
Diam. intérieur	120 mm
Diam. extérieur	165 mm
Épaisseur	45 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE