

Roulement à aiguilles
TRU153320-UU-IKO - TRU153320-UU-IKO


https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/tru153320-uu-iko



ROLLER BEARINGS

Caged Roller Bearings **With Seal**

Full Complement Roller Bearings **With Seal**



NAU49-UU
TRU-UU

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ₁ (1)	J
15	—	—	TRU 153320UU	80.5	15	33	20	0.3	19.5
	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (2)						
	N	N	rpm						
27	10 400	10 400	9 500						

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952385853
Diam. intérieur	15 mm
Diam. extérieur	33 mm
Epaisseur	20 mm
Conditionnement	1

contact@123roulement.be
02 808 18 02
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE