




Roulement à aiguilles TRU8511850-UU-IKO - TRU8511850-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/tru8511850-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings 
Full Complement Roller Bearings 



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r _{ext} ⁽¹⁾	J
85	---	---	TRU 8511850UU	1 530	85	118	50	1	94.5
E_w	N	N							
	114 000	222 000	2 000						

Notes^(*) Minimum allowable value of chamfer dimension r
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386508
Diam. intérieur	85 mm
Diam. extérieur	118 mm
Épaisseur	50 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE