


Roulement à aiguilles NAU4919-UU-IKO - NAU4919-UU-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nau4919-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
95	---	NAU 4919UU	1 270	95	130	35	1.5	106
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
120.5	N	N	rpm	81 000	136 000	1 800		

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386560
Diam. intérieur	95 mm
Diam. intérieur	3.74" inch
Diam. extérieur	130 mm
Diam. extérieur	5.118" inch
Epaisseur	35 mm
Epaisseur	1.378" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE