


Roulement à aiguilles NAS5028-ZZ-NR-IKO - NAS5028-ZZ-NR-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nas5028-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
140		NAS 5028ZZNR	11.0	140	210	218.4	95	94	77	8.5
f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
3	3	1	167	543 000	1 070 000	700				

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952387048
Diam. intérieur	140 mm
Diam. extérieur	210 mm
Épaisseur	95 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE