

## Roulement à aiguilles NAS5044-ZZ-NR-IKO - NAS5044-ZZ-NR-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nas5044-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number |              | Mass (Ref.) kg | Boundary dimensions mm |     |                |     |     |                |      |
|---------------|-----------------------|--------------|----------------|------------------------|-----|----------------|-----|-----|----------------|------|
|               | Sealed type           | Shield type  |                | d                      | D   | D <sub>2</sub> | B   | C   | C <sub>1</sub> | S    |
| 220           |                       | NAS 5044ZZNR | 52.0           | 220                    | 340 | 356            | 160 | 159 | 130            | 14.5 |

  

| f | c | r <sub>s</sub> mm <sup>(1)</sup> | J <sub>r</sub> | Basic dynamic load rating C <sub>r</sub> N | Basic static load rating C <sub>0</sub> N | Allowable rotational speed <sup>(2)</sup> rpm |
|---|---|----------------------------------|----------------|--|---|---|
| 6 | 4 | 1.5                              | 260            | 1 510 000                                  | 3 110 000                                 | 450   |

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952387208 |
| Diam. intérieur | 220 mm        |
| Diam. extérieur | 340 mm        |
| Épaisseur       | 160 mm        |
| Conditionnement | 1             |

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE