

Roulement à aiguilles NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nax6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Identification number					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g
60		NAX 6040Z	454	---	---	---
Boundary dimensions mm						
F_w	D	D_1	D_2	L	H	r
60	72	85	86.5	40	17	12
Basic load ratings						
Basic dynamic load rating C		Basic static load rating C_0		Allowable rotational speed ⁽²⁾		
Radial		Axial		rpm		
47 500		41 400		4 000		

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390376
Diam. intérieur	60 mm
Diam. extérieur	72 mm
Épaisseur	40 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE