


## Roulement à aiguilles NBX6040-IKO - NBX6040-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nbx6040-iko>

**IKO**

**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



Identification number													
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g							
60	---	---	---	NBX 6040		501							
Boundary dimensions mm													
$F_w$	$D$	$D_1$	$D_2$	$E$	$H$	$l_1$	$r_{s \text{ min}}$	$d_f$	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(2)</sup> rpm		
60	72	85	86.5	40	17	12	1	60	47 500	64 600	103 000	224 000	4 000

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension  $r$   
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:  
 1. The outer ring has an oil groove and an oil hole.  
 2. Grease is not prepacked. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390536
Diam. intérieur	60 mm
Diam. intérieur	2.362" inch
Diam. extérieur	72 mm
Diam. extérieur	2.835" inch
Epaisseur	40 mm
Epaisseur	1.575" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE