

Roulement à aiguilles NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nax7040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g	
	With dust cover	Without Inner Ring	With dust cover	Without Inner Ring	With dust cover	Without Inner Ring	With dust cover	Without Inner Ring
70		NAX 7040Z	606					

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	
F _w	D	D ₁	D ₂	L	H	l ₁	r _{s min.}	d _i	d _s		Radial	Axial		Radial
70	85	95	96.5	40	18	11	1	70	85	55 500	43 100	120 000	101 000	3 500

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390550
Diam. intérieur	70 mm
Diam. extérieur	85 mm
Épaisseur	40 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE