

## Roulement à aiguilles NBXI1223Z-IKO - NBXI1223Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nbxi1223z-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing With Inner Ring  
Needle Bearings with Thrust Roller Bearing With Inner Ring

Identification number														
		Mass (Ref.) g	With dust cover	Mass (Ref.) g			Mass (Ref.) g	With dust cover	Mass (Ref.) g					
					<b>NBXI 1223Z</b>		63			<b>12</b>				
Boundary dimensions mm			Bore diameter mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>	Assemble				
B	H	I <sub>1</sub>	r <sub>ms</sub>	r <sub>ms</sub>	Radial	Axial	Radial	Axial	rpm	LRT 1				
16.5	9	6.5	0.3	0.3	15	15	26	14	12 300	10 200	14 900	23 900	14 000	LRT 1

Minimum allowable value of chamfer dimension r  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.  
The outer ring has an oil groove and an oil hole.  
Bearing is not prepacked. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390710
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	23 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE