

## Roulement à aiguilles NBXI1730Z-IKO - NBXI1730Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nbxi1730z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification Number											
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D <sub>1</sub>		
17	---	---	---	---	---	---	<b>NBXI 1730Z</b>	111	17	30	35

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r	d <sub>4</sub>	d <sub>5</sub>	Radial	Axial		Radial	Axial			rpm
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17 600	19 000	25 400	48 700	11 000	<b>LRT 172020</b>

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: Z: The outer ring has an oil groove and an oil hole.  
1: Grease is not prepacked. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390796
Diam. intérieur	17 mm
Diam. extérieur	30 mm
Épaisseur	30 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE