

Roulement à aiguilles NBXI2030Z-IKO - NBXI2030Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nbxi2030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification Number																
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	d	D	D ₁				
	20	---	---	---	---	---	---	---					NBXI 2030Z	175	20	37
Boundary dimensions mm			Load limits		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	B	H	I ₁	r _{min}	F _w	d ₄	d ₅		Radial	Axial	Radial	Axial	LRT 202520		
43	30	20.5	11	9.5	0.6	0.3	25	25	40	24	20 000	22 700	32 100	60 700	9 000	LRT 202520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390833
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE