

Roulement à aiguilles NBXI2530Z-IKO - NBXI2530Z-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/nbxi2530z-iko>

UNIDIRECTIONAL TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number															
		Mass (Ref.) g	With dust cover	Mass (Ref.) g			Mass (Ref.) g	With dust cover	Mass (Ref.) g			d			
							NBXI 2530Z		200			25			
Boundary dimensions mm				Bore diameter mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾	Assemble				
B	H	I ₁	r _{ms}	r _{ms}	d _a	d _b	Radial	Axial	Radial	Axial	rpm	LRT			
20.5	11	9.5	0.6	0.3	30	45	25	100	27	400	40	100	81 000	8 000	LRT

(1) Minimum allowable value of chamfer dimension r. Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series. The outer ring has an oil groove and an oil hole. Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390871
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Épaisseur	30 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE