

## Roulement à aiguilles NAXI4032-IKO - NAXI4032-IKO

<https://www.123roulement.be/roulement-palier/roulement-aiguilles/aiguilles/naxi4032-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D <sub>i</sub>						
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g									
40	<b>NAXI 4032</b>	315	---	---	---	---	40	58	65						
Boundary dimensions mm		Lead-in chamfer mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRT 404520							
D <sub>2</sub>	L		B	H	I <sub>1</sub>	r			F <sub>w</sub>	d <sub>4</sub>	d <sub>5</sub>	Radial	Axial	Radial	Axial
66.5	32	20	14	9	0.6	0.3	45	57	44	31 000	27 900	60 200	55 100	5 000	LRT 404520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390963
Diam. intérieur	40 mm
Diam. extérieur	58 mm
Épaisseur	32 mm
Conditionnement	-

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE