


## Rotule GE SB9014076-IKO - SB9014076-IKO

<https://www.123roulement.be/roulement-palier/rotule/ge/sb9014076-iko>

IKO  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass. (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree	
			d	D	B	C	d <sub>k</sub>	r <sub>1</sub> mm <sup>(1)</sup>	α
90	SB 9014076	4.71	90	140	76	65	130	0.6	5
Mounting dimensions mm		Dynamic load capacity		Static load capacity					
d <sub>s</sub>	D <sub>s</sub>	C <sub>d</sub>	C <sub>s</sub>						
Min.	Max. <sup>(2)</sup>	Min.	N						
94.5	105.5	135.5	121	829 000	4 970 000				

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391496
Diam. intérieur	90 mm
Diam. extérieur	140 mm
Épaisseur	76 mm
Type	GE
Lubrification	sans
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE